

19" Pandora Soho Series Wall Mount Cabinets



Pandora Soho Wall Mount Cabinet 7U/9U/12U W540xD400mm

Multi folded modular design clamped with screws, coated with RAL 7035 epoxy polyester powder.

Front door with 4,0 mm thick Smoke Tinted-Antistatic-Tempered Glass compatible with EN 12150-1 has a single point lock type "O".

Completely standard and stocked product portfolio, being delivered as a single piece flat pack product, as standard shipping configuration 1 set: 2pieces 19" adjustable depth equipment mounting rails are included.

Cable entry available in top and bottom case W:145mm x D:70mm sized PVC cabling insertions.

Removable PVC cable entry covering, with the option of brush strip cover to provide dust protection.

Ventilation slots for active and passive ventilation are available on the top side (2 fans can be installed).

Maximum load capacity up to 60 kg.

Production Standards :

- ISO 9001:2015 - Quality Management System
- ISO 14001:2015 - Environmental Management System
- ISO 45001- Occupational Health and Safety Management System

Compliance:

- EN IEC 60297- Mechanical constructions for electronical devices. mechanical constructions (19 inch series) with standard universal 482,6 mm profiles
- EN IEC 60917- Modular layout for development of mechanical constructions in electronic equipment applications.
- EIA/ ECA-310 (D/E) 19" 482,6 mm and U 44,45 mm Height Sizing
- EN 61587-1 For electronic devices inner usage mechanic construction cabinets, bottom shelves, cases, IEC 60917 and IEC 60297 series tests, Chapter 1, environmental conditions, test setup and security rules.
- Climatic and environment: EN 61587-1/4.2, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-30
- Static Mechanical Load Lifting: EN 61587-1/5.2.1
- Dynamic mechanical load vibration and shock, impact: EN 61587-1/5.3.1, EN 61587-1/5.3.3, IEC 60068-2-6, IEC 60068-2-27
- Grounding: EN 61587-1/6.2
- Fireproofing: EN 61587-1/6.3
- IP protection class (IP code): IP20, EN 61587-1/6.4

